



Bear Woods

Supply Company | Since 1987

Blade Selection Chart



✓ Excellent/Recommended

- OK/Good

× Not recommended

Super Skip - 5"

Designed for hard and medium hardwoods, but also work perfectly on acrylics at lower speeds. The spaces between the teeth of these blades are wider than the normal skip tooth configuration, enabling the blade to cut very quickly while leaving a smooth finish. Surface sawdust is whisked away and edges remain clean.

	SKU	Univ. #	TPI	Cutting Trace (inches)	Hardwoods	Medium Hardwoods	Softwoods	Plywood	Corian/Plastics	Aluminum/Brass/Copper	Ferrous Metals	Optimal Thickness (inches)	Intricate	Tight	Light	Recommended Drill	Pilot Hole (inches)
	SSB-27	2/0	21.4	0.0098	✓	✓	-	-	✓	×	×	1/16" - 1/4"	✓			SSDB-070	0.0280
	SSB-28	0	19.3	0.0106	✓	✓	-	-	✓	×	×	3/32" - 1/4"	✓			SSDB-068	0.0310
	SSB-29	1	17.2	0.0114	✓	✓	-	-	✓	×	×	3/32" - 5/16"	✓			SSDB-064	0.0360
	SSB-30	2	16.1	0.0130	✓	✓	-	-	✓	×	×	1/8" - 13/32"	✓			SSDB-064	0.0360
	SSB-31	3	14.8	0.0138	✓	✓	-	-	✓	×	×	3/16" - 13/32"	✓			SSDB-060	0.0400
	SSB-32	4	13.8	0.0150	✓	✓	-	-	✓	×	×	7/32" - 1/2"		✓		SSDB-056	0.0430
	SSB-33	5	12.8	0.0157	✓	✓	-	-	✓	×	×	5/16" - 19/32"		✓		SSDB-056	0.4650
	SSB-35	7	11.3	0.0177	✓	✓	-	-	✓	×	×	13/32" - 25/32"		✓		SSDB-054	0.0530
	SSB-36	8	10.7	0.0185	✓	✓	-	-	✓	×	×	1/2" - 25/32"			✓	SSDB-054	0.0550
	SSB-37	9	10.1	0.0193	✓	✓	-	-	✓	×	×	1/2" - 1"			✓	SSDB-052	0.0635
	SSB-40	12	8.8	0.0244	✓	✓	-	-	✓	×	×	25/32" - 2"			✓	SSDB-050	0.0785

Hardwoods: beech, bloodwood, bocote, bubinga, canarywood, cocobolo, ebony, elm, hickory, hornbeam, jatoba, leopardwood, lyptus, marblewood, mora, oleaster, purpleheart, rosewood, wenge, yellowheart, zebrawood

Medium Hardwoods: ash, black cherry, cherry, eucalyptus, limba, macacauba, mahogany, maple, nogal, oak, padauk, redheart, sapele, teak, tzalam, walnut

Softwoods: alder, balsa, basswood, birch, black willow, chestnut, cedar, cypress, fir, larch, pine, poplar, redwood, Spanish cedar, spruce